

## BATTERY OPERATED PALLET TRUCK



Model	AT-1018-A	AT-1018-B
Product Size		
Capacity (kg)	2500	1500
Min. fork height (mm)	90	90
Max. fork height (mm)	200	200
Lifting height (mm)	110	110
Fork length (mm)	1150/1220	1150/1220
Single fork width (mm)	160	160
width over all forks (mm)	550/685	550/685
Fork wheel – tandem (mm)	80x70 PU	80x70 PU
Support wheel (mm)	180X70 PU	-
Driving wheel (mm)	230X70 PU	150x55 PU
Turning Radius (mm)	1810	1810
Travel Speed (Loaded/Unloaded) (km/h)	4.5/5.5	4.5/5.5
Lifting Speed (Loaded / Unloaded) (mm/sec)	22/30	22/30
Lowering Speed (Loaded / Unloaded) (mm/sec)	28/24	20/18
Type of Control	Rider Stand on Platform	Walkie

Traction Motor	24V, 1.5 kW	24V, 1 kW
Lift Motor	24V, 2 kW	24V, 1 kW
Battery - Voltage / Capacity	24V / 240 Ah	24V / 100 Ah
FEATURES	<ul style="list-style-type: none"> <li>- Overload Protection through pressure relief valve.</li> <li>- Operators Belly Switch for operator's protection.</li> <li>- Jerk free lifting and lowering.</li> <li>- Cutoff limit at top height to save energy and motor overheating.</li> </ul>	

***Note : Any changes to specifications or dimensions are possible. We should talk about the suggested application if these standards are important.***

altra