

LOW PROFILE SCISSOR LIFT TABLE



MODEL	AT-1035	
LOAD CAPACITY (KG)	500 - 2500	AS PER REQUIREMENT
MAX LIFTING HEIGHT (MM)	100 - 2000 (DEPENDS ON PLATFORM SIZE)	AS PER REQUIREMENT
MIN LOWER HEIGHT (MM)	180 - 250 (DEPENDS ON CAPACITY)	AS PER REQUIREMENT
PLATFORM SIZE (MM)	1000 X 1000 - 4000 X 3000	AS PER REQUIREMENT
OPERATING	AC ELECTRIC	AS PER REQUIREMENT
POWER PACK	2HP - 5HP	AS PER REQUIREMENT
FEATURES	<ul style="list-style-type: none"> - CARBURISED AND SURFACE HARDENED PINS WITH GUN METAL BUSHING INSIDE AT SCISSOR JOINTS. - HARD CHROM PLATED PISTON ROD AND HONED TUBES FOR CYLINDERS. - SIDE MOUNTED CYLINDERS. - SAFE HYDRAULIC WORKING WITH OVERLOAD PROTECTION. - ELECTRIC PANEL WITH MCB, CONTACTOR, OVERLOAD RELAY, SMPS FOR OPERATIONAL SAFETY. 	
ADDITIONAL FEATURES AVAILABLE	<ul style="list-style-type: none"> - RAILING ON TWO/THREE/FOUR SIDE OF PLATFORM. - SAFETY LIGHT CURTAINS. 	

	- FLAPS / RAMP AT ANY SIDE OF PLATFORM.
--	---

Note : Any changes to specifications or dimensions are possible. We should talk about the suggested application if these standards are important.

altra